

Etalon PARAGON - valeurs estimées viscosité cinématique mm²/s (cSt)

Part No.	20.00°C 68.00°F	25°C 77.00°F	37.78°C 100.00°F	40°C 104.00°F	50°C 122.00°F	60°C 140.00°F	80°C 176.00°F	98.89°C 210.00°F	100°C 212.00°F
N.4	0.4691	0.4495	0.4051	0.3981	-	-	-	-	-
N.8	0.7286	0.6903	0.6080	0.5954	-	-	-	-	-
N1.0	1.302	1.213	1.025	0.9976	0.8884	-	-	-	-
N2	2.984	2.687	2.110	2.031	1.726	1.490	-	-	-
S3	4.601	4.058	3.055	2.920	2.417	2.041	1.522	1.207	1.192
D5	6.497	5.623	4.060	3.856	3.113	2.573	1.860	1.439	1.420
S6	10.46	8.8869	6.117	5.772	4.528	3.655	2.540	1.913	1.885
N7.5	12.34	10.45	7.163	6.748	5.263	4.220	2.902	2.167	2.131
D10	14.63	12.18	8.075	7.572	5.799	4.583	3.086	2.273	2.236
N10	20.92	17.05	10.79	10.05	7.479	5.775	3.749	2.693	2.646
N14	30.54	24.46	14.87	13.76	9.977	7.529	4.713	3.304	3.241
S20	42.73	33.65	19.68	18.10	12.82	9.476	5.734	3.924	3.845
N26	61.14	49.10	29.80	27.53	19.81	14.79	9.020	6.160	6.034
N35	86.53	65.98	35.89	32.62	22.01	15.61	8.824	5.747	5.620
N44	114.3	88.50	49.33	44.98	30.57	21.69	12.16	7.801	7.619
S60	155.3	115.2	58.80	52.93	34.24	23.41	12.47	7.773	7.582
N75	203.9	155.5	83.66	75.81	50.25	34.86	18.79	11.70	11.41
N100	329.6	237.2	112.9	100.5	62.05	40.68	20.23	11.99	11.67
N140	409.6	305.9	156.8	141.1	90.53	60.96	31.22	18.68	18.17
S200	653.2	459.4	206.4	182.1	108.0	68.32	31.97	18.11	17.58
N250	779.6	572.7	283.0	252.8	158.2	104.0	51.12	29.56	28.71
D500	834.5	582.0	256.6	225.7	132.0	82.48	37.77	21.05	20.41
N350	1240	850.7	361.7	316.1	180.4	110.1	48.51	26.26	25.42
N415	1340	967.8	459.4	408.2	248.7	159.9	75.39	42.24	40.96
D1000	1717	1170	487.4	424.5	238.6	143.5	61.57	32.60	31.54
S600	2179	1468	595.4	516.4	285.0	168.9	70.50	36.63	35.38
N750	2746	1925	852.4	749.0	435.3	268.3	117.8	62.52	60.45
N1000	4489	2980	1162	1001	534.9	306.9	120.8	59.67	57.51
N1400	5608	3822	1586	1378	764.3	451.5	184.4	92.50	89.13
S2000	8573	5566	2053	1752	899.4	497.2	182.9	85.90	82.53
D5000	10245	6670	2463	2101	1079	593.8	216.9	100.7	96.74
N2500	11658	7673	2905	2488	1293	719.0	265.2	123.1	118.2
D7500	13686	8817	3192	2713	1368	742.7	264.0	119.9	114.9
N4000	18184	11582	4088	3465	1718	916.5	316.1	140.1	134.1
N5100	26904	17187	6050	5110	2516	1330	446.9	192.9	184.5
S8000	37745	23822	8136	6853	3311	1724	560.5	235.9	225.3
N10200	54473	34453	11868	9992	4834	2504	805.9	333.2	318.1
N15000	74506	46451	15463	12954	6120	3102	962.0	385.9	367.7
N18000	103824	65017	21802	18279	8654	4391	1352	537.3	511.3
S30000	138056	85267	27723	23124	10717	5334	1586	612.3	581.5